



## DATA SHEET

### MP1890F RAMIE FIBRE PACKING IMPREGNATED WITH PTFE & SILICON OIL

#### DESCRIPTION

MP1890F is a long ramie fibre which is square and thoroughly impregnated with mineral grease and PTFE (or tallow) to make the packing pliable and resilient. A very white packing suited to use in the mid range of pH.

#### APPLICATIONS

MP1890F is ideally suited for use in the less demanding applications. It can service pumps, valves, plungers, to seal hot and cold water and brine. It is especially suitable for marine use. It is also suitable for use in oils and solvents. This packing has a good resistance to mildew, fungi and bacteria. Suitable for rotary, reciprocating and static service.

#### SIZES/AVAILABILITY

Size: 3 x 3mm through to 25 x 25mm. Larger sizes available upon request  
Thickness: 32mm to 40mm. Length as per customer requirement

#### PHYSICAL PROPERTIES

Colour	White
Construction	Inter-braided
pH Value	5 – 9
Temperature	-50°C to 140°C
Pressure	150Psi (1050Kpa)
Speed	2000 FPM (10m/sec)
MSDS	Available upon request

*Industrial Gaskets reserves the right to change or modify any of its products, no liability is entered into or given on any of the data provided. Consultation of a technician should be sought if in any doubt.*

*Industrial Gaskets reserves the right to change or modify any of its products, no liability is entered into or given on any of the data provided. Consultation of a technician should be sought if in any doubt.*