



Inflatable Pipe Plugs / Flow Stoppers: **OLS**

| Type: OLS | | 40/70* | 65/100* | 70/150* | 100/200-S* | 100/200* | 150/300* | 200/400* | 300/600* | 500/1000* | 500/1200 |
|----------------------|------|---------|---------|---------|------------|----------|----------|----------|----------|-----------|----------|
| Range | mm | 40-70 | 65-100 | 70-150 | 100-200 | 100-200 | 150-300 | 200-400 | 300-600 | 500-1000 | 500-1200 |
| | inch | 1,5-2,7 | 2,5-4 | 2,7-6 | 4-8 | 4-8 | 6-12 | 8-16 | 12-24 | 20-40 | 20-48 |
| Max. workin pressure | Bar | 1,5 | 1,5 | 1,5 | 3,0 | 3,0 | 3,0 | 3,0 | 3,0 | 3,0 | 3,0 |
| | PSI | 22 | 22 | 22 | 44 | 44 | 44 | 44 | 44 | 44 | 44 |
| Dmin | mm | 35 | 60 | 65 | 95 | 95 | 135 | 180 | 290 | 460 | 440 |
| | inch | 1,4 | 2,3 | 2,6 | 3,7 | 3,7 | 5,3 | 7,1 | 11,4 | 18,1 | 17,3 |
| Length | mm | 160 | 100 | 310 | 250 | 500 | 500 | 500 | 700 | 1000 | 1650 |
| | inch | 6,3 | 4 | 12,2 | 9,8 | 19,7 | 19,7 | 19,7 | 27,6 | 39,4 | 65,0 |
| Weight | kg | 0,35 | 0,2 | 0,55 | 1,1 | 2 | 2,3 | 4 | 9 | 20 | 52 |
| | LBS | 0,8 | 0,44 | 1,2 | 2,4 | 4,4 | 5,1 | 8,8 | 19,8 | 44,1 | 114,6 |

| Type: OLS | | 40/70 | | 65/100 | | 70/150 | | 100/200 S | | 100/200 | | 150/300 | | 200/400 | | 300/600 | | 500/1000 | | 500/1200 | | |
|-----------------------|------|-------------------|-----|--------|-----|--------|-----|-----------|-----|---------|-----|---------|-----|---------|-----|---------|-----|----------|-----|----------|-----|----|
| | | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | |
| Max. working pressure | | 1,5 | 22 | 1,5 | 22 | 1,5 | 22 | 3,0 | 44 | 3,0 | 44 | 3,0 | 44 | 3,0 | 44 | 3,0 | 44 | 3,0 | 44 | 3,0 | 44 | |
| Pipe diameter | | Max. backpressure | | | | | | | | | | | | | | | | | | | | |
| | mm | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | |
| | Inch | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | Bar | PSI | |
| | 40 | 1,5 | 0,9 | 13 | | | | | | | | | | | | | | | | | | |
| | 70 | 2,7 | 0,7 | 10 | 1,1 | 13 | 0,9 | 13 | | | | | | | | | | | | | | |
| | 100 | 4 | | | 0,8 | 12 | 0,8 | 12 | 2 | 29 | 2 | 29 | | | | | | | | | | |
| | 150 | 6 | | | | | 0,7 | 10 | 1,3 | 19 | 1,6 | 23 | 2 | 29 | | | | | | | | |
| | 180 | 7 | | | | | | | 0,7 | 10 | 1,4 | 20 | 1,7 | 23 | | | | | | | | |
| | 200 | 8 | | | | | | | 0,5 | 7 | 1,3 | 19 | 1,5 | 21 | 2 | 29 | | | | | | |
| | 300 | 12 | | | | | | | | | | | 1,1 | 13 | 1,8 | 25 | 2 | 29 | | | | |
| | 400 | 16 | | | | | | | | | | | | | 1,2 | 13 | 1,8 | 26 | | | | |
| | 500 | 20 | | | | | | | | | | | | | | 1,6 | 23 | 2 | 29 | 1,9 | 28 | |
| | 600 | 24 | | | | | | | | | | | | | | 0,9 | 13 | 1,9 | 28 | 1,9 | 28 | |
| | 700 | 27 | | | | | | | | | | | | | | | | 1,8 | 26 | 1,8 | 26 | |
| | 800 | 32 | | | | | | | | | | | | | | | | | 1,7 | 23 | 1,8 | 26 |
| | 900 | 35 | | | | | | | | | | | | | | | | | 1,1 | 13 | 1,7 | 25 |
| | 1000 | 40 | | | | | | | | | | | | | | | | | 0,5 | 6 | 1,7 | 25 |
| | 1200 | 48 | | | | | | | | | | | | | | | | | | | 0,8 | 12 |

INDUSTRIAL GASKETS (ABN): 54 901 938 739

PH: (08) 8276 4140 email: sales@industrialgaskets.com.au