



## Top Hats - Metric

<b>Nema Grade</b>	<b>Minlon</b>
<b>Thickness</b>	1/32"
<b>Resin</b>	Nylon
<b>Water Absorption</b>	0.7%
<b>Dielectric Strength</b>	420VPM
<b>Tensile Strength</b>	9,200 PSI
<b>Max Operating Temp</b>	250°F

Stock No.	Size	A Overall Length Millimetres	B Washer Thickness Millimetres	ØC Total Face Length Millimetres	ØD ID of Sleeve Millimetres	ØE OD of Sleeve Millimetres	ØF Wall Thickness
TOPHATM6	M6	16 ± 0.2	3 ± 0.2	18 ± 0.2	6.2 ± 0.2	8 ± 0.2	0.9
TOPHATM8	M8	18.5 ± 0.2	3 ± 0.2	18 ± 0.2	8.2 ± 0.2	10 ± 0.2	0.9
TOPHATM10	M10	21.5 ± 0.2	3 ± 0.2	22 ± 0.2	10.2 ± 0.2	12 ± 0.2	1
TOPHATM12	M12	30 ± 0.2	3 ± 0.2	26 ± 0.2	12.5 ± 0.2	14 ± 0.2	1
TOPHATM14	M14	34 ± 0.2	3 ± 0.2	22 ± 0.2	14.2 ± 0.2	15.5 ± 0.2	1
TOPHATM16	M16	34.5 ± 0.2	3 ± 0.2	35 ± 0.2	16.5 ± 0.2	18.5 ± 0.2	1
TOPHATM20	M20	40 ± 0.2	3 ± 0.2	37 ± 0.2	20.5 ± 0.2	21.6 ± 0.2	1
TOPHATM24	M24	44.4 ± 0.2	3 ± 0.2	46.5 ± 0.2	24.5 ± 0.2	26 ± 0.2	1
TOPHATM27	M27	57 ± 0.2	3 ± 0.2	50 ± 0.2	27.5 ± 0.2	29 ± 0.2	1
TOPHATM30	M30	82 ± 0.2	3 ± 0.2	60 ± 0.2	30.5 ± 0.2	31.5 ± 0.2	1
TOPHATM33	M33	94 ± 0.2	3 ± 0.2	61 ± 0.2	34 ± 0.2	35 ± 0.2	1

**Material : Mineral Filled Nylon (Minlon)**

**Email: [sales@industrialgaskets.com.au](mailto:sales@industrialgaskets.com.au)**

**Telephone: (08) 8276 4140**