



PURE GUM RUBBER CORD

35 Shore | Natural Rubber

FEATURES

Gum Rubber Cord is a 35 Shore light brown Natural Rubber compound designed for extrusion.

TECHNICAL INFORMATION

Temperature (Max)	-40°C to +70°C	
Tensile Strength	11.96 MPa (min)	ASTM D2240
Elongation at Break	700 % (min)	ASTM D412
Hardness	35° ± 5° Shore A	ASTM D2240
Specific Gravity	1.08	ASTM D297
Test Condition	Laboratory Temperature +23°C	HUMIDITY UNKNOWN
Colour	Light Brown / Tan	
MSDS	Available upon request	

AVAILABLE SIZES

STANDARD THICKNESS

3mm, 4mm, 5mm, 6.5mm, 8mm, 10mm, 13mm, 16mm, 19mm, 22mm, 25mm and 32mm

AVAILABLE STYLES

EPDM, Nitrile, Neoprene and Silicone



APPLICATIONS

Pure Gum Natural Rubber Cord is usually Tan or Black and made by using an organic material and is very resilient by not holding a shape and is self healing.

Pure Gum Natural Rubber Cord is an elasticised duro 35 natural rubber designed to withstand abrasion, tear and cutting. Industrial Gaskets Pure Gum Natural Rubber Cord is used in:

- > Seals
- > Drum pads
- > Gaskets

That require both bounce and stretch capability